

# 844

## Product Transfer Account Adjustment

Functional Group=**CF**

This Draft Standard for Trial Use contains the format and establishes the data contents of the Product Transfer Account Adjustment Transaction Set (844) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to transmit specific data in the form of a debit, credit, or request for credit relating to pre-authorized product transfer actions.

### Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	ST	Transaction Set Header	M	1			Must use
020	BAA	Beginning Segment for Product Transfer Account Adjustment	M	1			Must use
<b>LOOP ID - N1</b>					<b>50</b>		
070	N1	Name	O	1			Used

### Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
<b>LOOP ID - CON</b>					<b>10000</b>		
010	CON	Contract Number Detail	M	1			Must use
<b>LOOP ID - N1</b>					<b>50</b>		
050	N1	Name	M	1			Must use
070	N3	Address Information	M	2			Must use
080	N4	Geographic Location	M	1			Must use
<b>LOOP ID - SII</b>					<b>≥1</b>		
105	SII	Sales Item Information	M	1			Must use
107	N9	Reference Identification	M	1			Must use

### Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	CTT	Transaction Totals	M	1		N3/010	Must use
020	AMT	Monetary Amount	O	5			Used
030	SE	Transaction Set Trailer	M	1			Must use

### Notes:

3/010 Number of line items (CTT01) is the accumulation of the number of CON segments. If used, hash total (CTT02) is the sum of adjustment quantities (QTY02) for each QTY segment.

# ST Transaction Set Header

Pos: 010	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

**User Option (Usage):** Must use

To indicate the start of a transaction set and to assign a control number

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	<b>Transaction Set Identifier Code</b>	M	ID	3/3	Must use
		<b>Description:</b> Code uniquely identifying a Transaction Set				
		<u>Code</u>		<u>Name</u>		
		844		Product Transfer Account Adjustment		
ST02	329	<b>Transaction Set Control Number</b>	M	AN	4/9	Must use
		<b>Description:</b> Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set				

## Semantics:

1. The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

# BAA Beginning Segment for Product Transfer Account Adjustment

Pos: 020	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 5

**User Option (Usage):** Must use

To identify the beginning of a Product Transfer Account Adjustment Transaction Set and further define the type of product account adjustment transaction set and its reference number and date

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BAA01	353	<b>Transaction Set Purpose Code</b>	M	ID	2/2	Must use
		<b>Description:</b> Code identifying purpose of transaction set				
		<u>Code</u>		<u>Name</u>		
		00		Original		
BAA02	640	<b>Transaction Type Code</b>	M	ID	2/2	Must use
		<b>Description:</b> Code specifying the type of transaction				
		<u>Code</u>		<u>Name</u>		
		RA		Request for Credit		
BAA03	373	<b>Date</b>	M	DT	8/8	Must use
		<b>Description:</b> Date expressed as CCYYMMDD				
BAA04	128	<b>Reference Identification Qualifier</b>	X	ID	2/3	Used
		<b>Description:</b> Code qualifying the Reference Identification				
		<u>Code</u>		<u>Name</u>		
		AM		Adjustment Memo (Charge Back)		
BAA05	127	<b>Reference Identification</b>	X	AN	1/30	Used
		<b>Description:</b> Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier				

## Syntax Rules:

1. P0405 - If either BAA04 or BAA05 is present, then the other is required.

## Semantics:

1. BAA03 is the account adjustment date.
2. BAA06 is the account adjustment time.

# Loop N1

Pos: 070	Repeat: 50
Optional	
Loop: N1	Elements: N/A

**User Option (Usage):** Used

To identify a party by type of organization, name, and code

## Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
070	N1	Name	O	1		Used

# N1

# Name

Pos: 070	Max: 1
Heading - Optional	
Loop: N1	Elements: 4

**User Option (Usage):** Used

To identify a party by type of organization, name, and code

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	<b>Entity Identifier Code</b>	M	ID	2/3	Must use
		<b>Description:</b> Code identifying an organizational entity, a physical location, property or an individual				
		<u>Code</u>		<u>Name</u>		
		DB		Distributor Branch		
		DS		Distributor		
		MF		Manufacturer of Goods		
N102	93	<b>Name</b>	X	AN	1/60	Used
		<b>Description:</b> Free-form name				
N103	66	<b>Identification Code Qualifier</b>	X	ID	1/2	Used
		<b>Description:</b> Code designating the system/method of code structure used for Identification Code (67)				
		<u>Code</u>		<u>Name</u>		
		11		Drug Enforcement Administration (DEA)		
N104	67	<b>Identification Code</b>	X	AN	2/80	Used
		<b>Description:</b> Code identifying a party or other code				

## Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

## Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

# Loop CON

<b>Pos: 010</b>	<b>Repeat: 10000</b>
<b>Mandatory</b>	
<b>Loop: CON Elements: N/A</b>	

**User Option (Usage):** Must use

To specify contract or reference number and status

## Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	CON	Contract Number Detail	M	1		Must use
050		Loop N1	O		50	Used

# CON Contract Number Detail

Pos: 010	Max: 1
Detail - Mandatory	
Loop: CON	Elements: 3

**User Option (Usage):** Must use

To specify contract or reference number and status

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CON01	128	<b>Reference Identification Qualifier</b>	M	ID	2/3	Must use
		<b>Description:</b> Code qualifying the Reference Identification				
		<u>Code</u>		<u>Name</u>		
		VC		Vendor Contract Number		
CON02	127	<b>Reference Identification</b>	M	AN	1/30	Must use
		<b>Description:</b> Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier				
CON03	846	<b>Contract Status Code</b>	M	ID	2/2	Must use
		<b>Description:</b> Code designating the current status of the contract				
		<u>Code</u>		<u>Name</u>		
		VA		Valid Open Contract		

# Loop N1

Pos: 050	Repeat: 50
Optional	
Loop: N1	Elements: N/A

**User Option (Usage):** Used

To identify a party by type of organization, name, and code

## Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
050	N1	Name	M	1		Must use
070	N3	Address Information	M	2		Must use
080	N4	Geographic Location	M	1		Must use
105		Loop SII	O		>1	Used



**N1****Name**

<b>Pos: 050</b>	<b>Max: 1</b>
<b>Detail - Mandatory</b>	
<b>Loop: N1</b>	<b>Elements: 4</b>

**User Option (Usage):** Must use

To identify a party by type of organization, name, and code

**Element Summary:**

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	<b>Entity Identifier Code</b>	M	ID	2/3	Must use
		<b>Description:</b> Code identifying an organizational entity, a physical location, property or an individual				
		<u>Code</u>		<u>Name</u>		
		ST		Ship To		
N102	93	<b>Name</b>	X	AN	1/60	Used
		<b>Description:</b> Free-form name				
N103	66	<b>Identification Code Qualifier</b>	X	ID	1/2	Must use
		<b>Description:</b> Code designating the system/method of code structure used for Identification Code (67)				
		<u>Code</u>		<u>Name</u>		
		11		Drug Enforcement Administration (DEA)		
		21		Health Industry Number (HIN)		
N104	67	<b>Identification Code</b>	X	AN	2/80	Must use
		<b>Description:</b> Code identifying a party or other code				

**Syntax Rules:**

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

**Comments:**

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

# N3 Address Information

Pos: 070	Max: 2
Detail - Mandatory	
Loop: N1	Elements: 1

**User Option (Usage):** Must use

To specify the location of the named party

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N301	166	<b>Address Information</b>	M	AN	1/55	Must use

**Description:** Address information

# N4 Geographic Location

Pos: 080	Max: 1
Detail - Mandatory	
Loop: N1	Elements: 4

**User Option (Usage):** Must use

To specify the geographic place of the named party

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	<b>City Name</b>	O	AN	2/30	Used
		<b>Description:</b> Free-form text for city name				
N402	156	<b>State or Province Code</b>	O	ID	2/2	Used
		<b>Description:</b> Code (Standard State/Province) as defined by appropriate government agency				
N403	116	<b>Postal Code</b>	O	ID	3/15	Used
		<b>Description:</b> Code defining international postal zone code excluding punctuation and blanks (zip code for United States)				
N404	26	<b>Country Code</b>	O	ID	2/3	Used
		<b>Description:</b> Code identifying the country				

## Syntax Rules:

1. C0605 - If N406 is present, then N405 is required.

## Comments:

1. A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
2. N402 is required only if city name (N401) is in the U.S. or Canada.

# Loop SII

Pos: 105	Repeat: >1
Optional	
Loop: SII	Elements: N/A

**User Option (Usage):** Used

To specify line item information related to a sale of an item

## Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
105	SII	Sales Item Information	M	1		Must use
107	N9	Reference Identification	M	1		Must use

# SII Sales Item Information

Pos: 105	Max: 1
Detail - Mandatory	
Loop: SII	Elements: 7

**User Option (Usage):** Must use

To specify line item information related to a sale of an item

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SII01	235	<b>Product/Service ID Qualifier</b>	M	ID	2/2	Must use
		<b>Description:</b> Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		<b>Code</b>		<b>Name</b>		
		N4		National Drug Code in 5-4-2 Format		
		VC		Vendor's (Seller's) Catalog Number		
SII02	234	<b>Product/Service ID</b>	M	AN	1/48	Must use
		<b>Description:</b> Identifying number for a product or service				
SII03	380	<b>Quantity</b>	M	R	1/15	Must use
		<b>Description:</b> Numeric value of quantity				
SII04	C001	<b>Composite Unit of Measure</b>	M	Comp		Must use
		<b>Description:</b> To identify a composite unit of measure(See Figures Appendix for examples of use)				
	355	<b>Unit or Basis for Measurement Code</b>	M	ID	2/2	Must use
		<b>Description:</b> Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken				
		<b>Code</b>		<b>Name</b>		
		EA		Each		
SII05	212	<b>Unit Price</b>	O	R	1/17	Used
		<b>Description:</b> Price per unit of product, service, commodity, etc.				
SII06	212	<b>Unit Price</b>	O	R	1/17	Used
		<b>Description:</b> Price per unit of product, service, commodity, etc.				
SII07	782	<b>Monetary Amount</b>	O	R	1/18	Used
		<b>Description:</b> Monetary amount				

## Semantics:

1. SII03 is the amount of the product identified in SII01 and SII02.
2. SII05 is the wholesale acquisition price.
3. SII06 is the contract price.
4. SII07 is the extended rebate amount.

# N9 Reference Identification

Pos: 107	Max: 1
Detail - Mandatory	
Loop: SII	Elements: 3

**User Option (Usage):** Must use

To transmit identifying information as specified by the Reference Identification Qualifier

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N901	128	<b>Reference Identification Qualifier</b>	M	ID	2/3	Must use
<b>Description:</b> Code qualifying the Reference Identification						
		<b><u>Code</u></b>	<b><u>Name</u></b>			
		DI	Distributor Invoice Number			
N902	127	<b>Reference Identification</b>	X	AN	1/30	Used
<b>Description:</b> Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier						
N904	373	<b>Date</b>	O	DT	8/8	Used
<b>Description:</b> Date expressed as CCYYMMDD						

## Syntax Rules:

1. R0203 - At least one of N902 or N903 is required.
2. C0605 - If N906 is present, then N905 is required.

## Semantics:

1. N906 reflects the time zone which the time reflects.
2. N907 contains data relating to the value cited in N902.

# CTT Transaction Totals

Pos: 010	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 1

**User Option (Usage):** Must use

To transmit a hash total for a specific element in the transaction set

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	Number of Line Items	M	NO	1/6	Must use

**Description:** Total number of line items in the transaction set

## Syntax Rules:

1. P0304 - If either CTT03 or CTT04 is present, then the other is required.
2. P0506 - If either CTT05 or CTT06 is present, then the other is required.

## Comments:

1. This segment is intended to provide hash totals to validate transaction completeness and correctness.

# AMT Monetary Amount

Pos: 020	Max: 5
Summary - Optional	
Loop: N/A	Elements: 2

**User Option (Usage):** Used

To indicate the total monetary amount

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
AMT01	522	<b>Amount Qualifier Code</b>	M	ID	1/3	Must use
		<b>Description:</b> Code to qualify amount				
		<u>Code</u>		<u>Name</u>		
		CC		Chargeback Claim Amount		
AMT02	782	<b>Monetary Amount</b>	M	R	1/18	Must use
		<b>Description:</b> Monetary amount				



# SE Transaction Set Trailer

Pos: 030	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

**User Option (Usage):** Must use

To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	<b>Number of Included Segments</b>	M	NO	1/10	Must use
		<b>Description:</b> Total number of segments included in a transaction set including ST and SE segments				
SE02	329	<b>Transaction Set Control Number</b>	M	AN	4/9	Must use
		<b>Description:</b> Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set				

## Comments:

1. SE is the last segment of each transaction set.